

Forte Ultra



PRODUCES HIGH-QUALITY PRODUCT FROM THE CORE TO THE TAIL

KEY ADVANTAGES

- Ultimate availability and productivity
- Clean and reliable transfer
- Robust and flexible perforator
- Near zero tension with minimal nips
- High quality product throughout the wind

MAJOR OPTIONS

- Premium wind package
- Second perforator package
- Core position control guides
- Plybonder

SPECIFICATIONS

Maximum web speed	2.9m: 800mpm (2625fpm)
	3.3m: 800mpm (2625fpm)
	3.7m: 700mpm (2297fpm)
Cycle rate	2.9m: 60 logs/min
	3.3m: 55 logs/min
	3.7m: 50 logs/min
Web width range	2.9m: 2450-2850mm (96.5-112.2")
	3.3m: 2850-3250mm (112.2"-128.0")
Core diameter ranges	25-40mm (0.98-1.57")
	38-60mm (1.50-2.36")
Log diameter ranges	90-160mm (3.54-6.30")
	90-200mm (3.54-7.87 in)

Forte V Rewinder



DESIGNED FOR THE CONVERTER PRODUCING ROLLS FOR THE VALUE MARKET

KEY ADVANTAGES

- The most open design available
- Clean and reliable transfer
- Robust and flexible perforator

MAJOR OPTIONS

- Plybonder
- Rubber-to-steel embosser

SPECIFICATIONS

Maximum web speed	550mpm (1804fpm)
	610mpm (2001fpm)
Cycle rate:	45 logs/min.
Core diameter range:	38-60mm (1.50-2.36")
Core length range:	2450-2850mm (96.5-112.2")
Log diameter range:	90-160mm (3.54-6.30")