



PRODUCES HIGH-QUALITY PRODUCT FROM THE CORE TO THE TAIL

KEY ADVANTAGES

- Ultimate availability and productivity
- Clean and reliable transfer
- Robust and flexible perforator
- Near zero tension with minimal nips
- High quality product throughout the wind

MAJOR OPTIONS

- Premium wind package
- Second perforator package
- Mandrel position control guides

SPECIFICATIONS

Maximum web speed	360mpm (1181fpm)
Cycle rate	Up to 320 rolls/minute
Mandrel diameter range	32-40mm (1.25-1.57")
Roll diameter range	62-92mm (2.44-3.62")
Variable perforator	Infinite perf range

SALES CONTACTS

EUROPE, MIDDLE EAST:

Virginio Losi / +41 79 916 99 80 / Virginio.Losi@pcmc.com

SOUTH AMERICA, CENTRAL AMERICA, CARRIBEAN, MEXICO, AFRICA, FAR WEST EUROPE:

José Carlos Ávila / +55 13 99741 0441 / Josecarlos.Avila@pcmc.com

NORTH AMERICA, ASIA, OCEANIA:

Mike Callahan / +1 920.336.0116 / Mike.Callahan@pcmc.com

JAPAN:

Taihei Kashibe / + 81.45.671.5461 / Taihei.Kashibe@pcmc.co.jp