

HUDSON-SHARP

Ares 400 Series Comparison

	ARES 400 LITE	ARES 400 ELITE	ARES 400 RAPID
Max Speed	150 CPM	150 CPM	200 CPM
Overall Length	39 ft / 11.9 m	43 ft / 13.1 m	51 ft / 15.5 m
Standard Pouch Formats	SUP / 3SS / 2SS	SUP / 3SS / 2SS	SUP / 3SS / 2SS
Optional Pouch Formats	bottom fill	bottom fill / inserted gusset	bottom fill
Single 40 in / 1016 mm Diameter Unwind	X	X	X
Intermittent Longitudinal Sealer	X	X	X
10 mm Flange Zipper	X	X	X
Independent K-Sealers		X	X
Ultrasonic Zipper Crush	X	X	X
# Cross Sealers	3	3	5
# Cross Coolers	1	1	2
Midfeed Nips	1	1	2
Tear Notch/Hanger Hole/Round Corner Punch	X	X	X
Auto-Correction		X	X
Flying Knife Cut-Off w/Double Cut	X	X	X
74 in / 1880 mm Index Conveyor	X	X	
Two-Tier Index Conveyor		X	X
Pack-off Counter	○	X	X
OPTIONS:			
Front/Back Web Registration		○	
30 in / 762 mm Diameter Two-Position Unwind	○	○	○
Air Turn Bar for Inline Unwind	○	○	○
6 in / 152.4 mm Core Shafts	○	○	○
3 in to 6 in / 76.2 mm to 152.4 mm Adaptors	○	○	○
Center Guide on Unwind	○	○	○
Line Guide on Unwind	○	○	○
Continuous Longitudinal Sealer		requires edge sealer	requires edge sealer
Edge Sealer	○	○	○
Ultrasonic Zipper w/Hot Crush		○	○
Child Resistant Zipper + Hot Crush	○	○	○
Auto-Correction	○		
Auto-Position + Auto-Correction		○	○
Guillotine Cut-Off	○	○	○

Ares 400 Lite = Entry level, essential options, smallest footprint

Ares 400 Elite = More standard features, most versatility, K-sealers for fast changeovers

Ares 400 Rapid = Highest output speed, fast changeovers, fewer options